Data Sheet
Date: 03/21/2017

WPL EYELED CEL x3 ADJ 36W 2.7K 40D WHT



Item code	41400034
Product family	EYELED
Series	CEILING
Fixture voltage (V)	220-240
Fixture current (mA)	0.6
Fixture power (W)	3x36
CCT (K)	2700



General Characteristics

Power supply	INSIDE
Led power (W)	3x33
Fixture power (W)	3x36
CCT (K)	2700
Beam opening (°)	40
Orientability (°)	340 - 90
Colour type	WARM WHITE
LED type	COB

Wiva Group S.p.A. - via Siena, 47/37 INT.29 - 50142 FIRENZE - TEL +39 055 7222449 - FAX +39 055 0133758 - info@wivagroup.com
All parts of this document are the property of Wiva Group SpA. All rights reserved. This document and the information included are provided without any responsibility deriving from errors or omissions. It is not possible to cut, copy or use part of this document without a written permission. Wiva Group reserves the right to make changes to the above data without prior notice for reasons due to improvements and product variations.

Dimensional Characteristics

Length (mm)	364
Width (mm)	124
Height (mm)	118

Performance


Led luminous flux (lm)	3x4220
Fixture luminous flux (lm)	3x3800
Led efficacy (lm/W)	128
Fixture efficacy (lm/W)	106
Luminous intencity (cd)	3x5590
CRI	85+
Average life time (h)	L80 50000h

Others characteristics

Environmental temperature range (°C)	-25 +40
IP prtection	20
Electric protection	II
Fire protection	F
Photobiological group	0

Wiva Group S.p.A. - via Siena, 47/37 INT.29 - 50142 FIRENZE - TEL +39 055 7222449 - FAX +39 055 0133758 - info@wivagroup.com
All parts of this document are the property of Wiva Group SpA. All rights reserved. This document and the information included are provided without any responsibility deriving from errors or omissions. It is not possible to cut, copy or use part of this document without a written permission. Wiva Group reserves the right to make changes to the above data without prior notice for reasons due to improvements and product variations.

Lighting performance



H[m]	D[m]	Max lux	Med lux	Alpha=17.3°+17.3°	G=00
1.00	0.62	5590	3360		
2.00	1.25	1398	840		
3.00	1.87	621	373		
4.00	2.49	349	210		
5.00	3.11	224	134		

All parts of this document are the property of Wiva Group SpA. All rights reserved. This document and the information included are provided without any responsibility deriving from errors or omissions. It is not possible to cut, copy or use part of this document without a written permission. Wiva Group reserves the right to make changes to the above data without prior notice for reasons due to improvements and product variations.

Shipment characteristics

Barcode	8054890171847
Inner box (pcs)	1
Master box (pcs)	--
Fixture weight (Kg)	--

The product is designed, manufactured, tested and verified in compliance to the following product European Directive, Regulation and Standards:

EN 61547, EN 55015, EN 61000-3-2, EN 61000-3-3, EN 62471, IEC TR 62471-2, EN 62031+A1+A2, EN 60598-1, EN 55015+A1

2014/30/EU, 2011/65/EU, 2012/19/EU, 2010/30/EU, 874/2012/EU, 2009/125/EC, 1194/2012/EU

Wiva Group S.p.A. - via Siena, 47/37 INT.29 - 50142 FIRENZE - TEL +39 055 7222449 - FAX +39 055 0133758 - info@wivagroup.com
All parts of this document are the property of Wiva Group SpA. All rights reserved. This document and the information included are provided without any responsibility deriving from errors or omissions. It is not possible to cut, copy or use part of this document without a written permission. Wiva Group reserves the right to make changes to the above data without prior notice for reasons due to improvements and product variations.