

WPL EYELED DWL SQ TRIMLESS ADJ 25W 4K 40D WHT



Item code	41110058
Product family	EYELED
Series	DOWNLIGHT
Fixture voltage (V)	37
Fixture current (mA)	700
Fixture power (W)	25
CCT (K)	4000



General Characteristics

Power supply	NOT_INCLUDED
Fixture voltage (V)	37
Fixture current (mA)	700
Fixture power (W)	25
CCT (K)	4000
Beam opening (°)	40
Orientability (°)	340 - 90
Colour type	NATURAL WHITE
LED type	COB

Dimensional Characteristics

Length (mm)	152
Width (mm)	152
Height (mm)	103
Cutting size (mm)	156x156

Performance

Led luminous flux (lm)	3450
Fixture luminous flux (lm)	3100
LED efficacy (lm/W)	138
Fixture efficacy (lm/W)	124
Luminous intensity (cd)	4560
CRI	85+
Average life time (h)	L80 50000h

Others characteristics

Environmental temperature range (°C)	-25 +40
IP prtction	20
Electric protection	III
Fire protection	F
Photobiological group	0

H[m]	D[m]	Max lux	Med lux	Alpha=17.3°+17.3°	G=00	
1.00	0.62	4560	2741			
2.00	1.25	1140	685			
3.00	1.87	507	305			
4.00	2.49	285	171			
5.00	3.11	182	110			

Wiva Group S.p.A. - via Siena, 47/37 INT.29 - 50142 FIRENZE - TEL +39 055 7222449 - FAX +39 055 0133758 - info@wivagroup.com
All parts of this document are the property of Wiva Group SpA. All rights reserved. This document and the information included are provided without any responsibility deriving from errors or omissions. It is not possible to cut, copy or use part of this document without a written permission. Wiva Group reserves the right to make changes to the above data without prior notice for reasons due to improvements and product variations.

Shipment characteristics

Barcode	8054890171472
Inner box (pcs)	1
Master box (pcs)	--
Fixture weight (Kg)	--

The product is designed, manufactured, tested and verified in compliance to the following product European Directive, Regulation and Standards:

EN 61547, EN 55015, EN 61000-3-2, EN 61000-3-3, EN 62471, IEC TR 62471-2, EN 62031+A1+A2, EN 60598-1, EN 60598-2-2, EN 55015+A1

2014/30/EU, 2011/65/EU, 2012/19/EU, 2010/30/EU, 874/2012/EU, 2009/125/EC, 1194/2012/EU